

屋内照明器具特性	
品番 (品名)	HH- CC1262A
光源	LED6200_70_5499 x1 5499.0 lm
管理番号	K0154966(0)D 1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	26	
	中 0.6	0.8	65	53	45	39	63	52	44	38	60	50	43	38	57	48	42	37	35	
	否 0.56	1.0	71	60	52	46	69	59	51	46	66	57	50	45	62	55	49	44	42	
			1.25	77	67	59	53	75	66	59	53	71	63	57	52	68	61	56	51	48
下方投影面積	cm ²	1.5	81	72	65	59	79	71	64	58	75	68	62	57	72	66	61	56	53	
		2.0	87	79	73	67	85	78	72	67	81	75	70	65	78	72	68	64	61	
取付高さ	器具間隔最大限		2.5	91	84	78	73	89	82	77	72	85	79	75	71	81	77	73	69	66
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	86	81	77	87	83	79	75	84	80	76	73	70
Hm	1.31Hm	1.32Hm	4.0	96	92	87	83	94	90	86	82	91	87	84	80	87	84	81	79	75
			5.0	98	94	91	87	97	93	89	86	93	90	87	84	89	87	84	82	78
			7.0	101	98	95	92	99	96	93	91	95	93	91	89	92	90	88	86	83
			10.0	103	100	98	96	101	99	97	95	97	96	94	92	94	93	91	90	86

