

屋内照明器具特性

品番 (品名)	XLJ 4301														
光源	LED5000_88_6900 x1 6900.0 lm														
管理番号	K0189570(0)DR1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	100%																				
保守率	良 中 否	0.86	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2	
		0.84	0.8	6.9	5.8	5.1	4.5	6.8	5.8	5.0	4.5	6.5	5.6	5.0	4.5	6.3	5.5	4.9	4.5	4.3	
			1.0	7.6	6.6	5.9	5.3	7.5	6.5	5.8	5.3	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.3	5.0	
		0.79	1.25	8.2	7.3	6.7	6.1	8.1	7.2	6.6	6.1	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.0	5.8	
下方投影面積	c m ²	1.5	8.6	7.8	7.2	6.7	8.5	7.7	7.2	6.7	8.2	7.5	7.0	6.6	7.9	7.4	6.9	6.6	6.3		
		2.0	9.2	8.5	8.0	7.6	9.0	8.4	7.9	7.5	8.7	8.2	7.8	7.4	8.5	8.0	7.7	7.3	7.1		
取付高さ	器具間隔最大限		2.5	9.5	9.0	8.5	8.1	9.4	8.9	8.4	8.1	9.1	8.6	8.3	8.0	8.8	8.5	8.1	7.9	7.6	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.3	8.9	8.5	9.6	9.2	8.8	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.5	8.2	8.0	
1.5m	1.94m	1.93m	4.0	10.0	9.7	9.3	9.0	9.9	9.5	9.2	9.0	9.6	9.3	9.1	8.8	9.4	9.1	8.9	8.7	8.4	
2	2.58	2.53	5.0	10.2	9.9	9.6	9.4	10.0	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.5	9.3	9.2	9.0	8.7	
2.5	3.22	3.16	7.0	10.4	10.2	10.0	9.8	10.2	10.0	9.8	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.5	9.3	9.1	
3	3.86	3.79	10.0	10.5	10.4	10.2	10.1	10.4	10.2	10.1	10.0	10.1	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.3	

