

屋内照明器具特性	
品番 (品名)	HH- CD0843AS
光源	LED6200_70_4299 x1 4299.0lm
管理番号	K0161883(0)D 1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	6%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	53	41	33	27	52	40	32	27	49	38	31	26	46	37	31	26	23
	中	0.6	0.8	63	51	43	37	61	50	42	37	58	48	41	36	55	46	40	35	33
	否	0.56	1.0	70	59	50	44	68	57	50	44	64	55	48	43	60	53	47	42	39
			1.25	76	66	58	52	74	64	57	51	70	62	55	50	66	59	53	49	46
下方投影面積	cm ²		1.5	80	71	63	57	78	69	62	57	74	66	60	55	70	64	58	54	51
等価発光面積	cm ²		2.0	86	78	71	66	84	76	70	65	79	73	68	63	76	70	66	62	58
取付高さ	器具間隔最大限		2.5	90	83	77	71	87	81	75	71	83	78	73	69	79	75	71	67	63
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	90	84	79	75	86	81	77	73	82	78	74	71	67
H _m	1.40H _m	1.39H _m	4.0	96	90	86	82	93	89	85	81	89	85	82	79	85	82	79	76	72
			5.0	98	93	90	86	95	92	88	85	91	88	85	82	88	85	82	80	76
			7.0	100	97	94	91	98	95	92	90	94	92	89	87	90	88	86	84	80
			10.0	102	100	97	95	100	98	96	94	96	94	92	91	92	91	89	88	83

