

# 屋内照明器具特性

品番 (品名)	HH- CD0871A	
光源	LED6200_70_4000 x1      4000.0 lm	
管理番号	K0164432(0)D 1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 14%		下方光束 86%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	53	41	33	28	51	40	33	27	48	38	31	27	44	36	30	26	23	
	中	0.6	0.8	63	51	43	38	61	50	42	37	56	47	41	36	52	44	39	34	31	
	否	0.56	1.0	70	59	51	45	67	57	49	44	62	54	47	42	58	51	45	41	37	
			1.25	75	65	58	52	73	63	56	51	67	60	54	49	63	56	51	47	43	
下方投影面積	cm <sup>2</sup>		1.5	79	70	63	57	77	68	62	56	71	64	59	54	66	61	56	52	47	
等価発光面積	cm <sup>2</sup>		2.0	85	77	71	66	82	75	69	64	77	71	66	62	71	67	63	59	54	
取付高さ	器具間隔最大限		2.5	89	82	76	71	86	79	74	70	80	75	71	67	75	71	67	64	58	
	横方向 (A)	縦方向 (B)	3.0	91	85	80	76	88	83	78	74	83	78	74	71	77	74	70	67	62	
H <sub>m</sub>	1.29H <sub>m</sub>	1.29H <sub>m</sub>	4.0	94	89	85	81	91	87	83	80	86	82	79	76	80	78	75	72	66	
			5.0	96	92	89	85	93	90	86	83	88	85	82	79	83	80	78	76	70	
			7.0	99	96	93	90	96	93	90	88	90	88	86	84	85	83	81	80	73	
			10.0	100	98	96	94	98	96	94	92	92	90	89	87	87	86	84	83	76	

