

屋内照明器具特性

品番 (品名)	HH- CD0880A									
光源	LED6200_70_4299 x1 4299.0 lm									
管理番号	K0161510(0)D 1									
BZ分類	BZ6/0.7/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	23%	床	10%				10%				10%				10%				0%	
下方光束	77%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	51	39	31	26	49	38	30	25	44	35	28	24	40	32	27	22	19	
		0.8	61	49	41	35	58	47	40	34	53	44	37	32	48	40	35	30	26	
		1.0	67	56	48	42	64	54	47	41	58	50	43	39	53	46	41	36	32	
		1.25	73	63	55	49	70	60	53	48	63	56	50	45	57	51	46	42	37	
下方投影面積	c m ²	1.5	77	68	61	55	74	65	59	53	67	60	55	50	61	55	51	47	41	
		2.0	83	75	68	63	79	72	66	61	72	67	62	57	66	61	57	54	47	
取付高さ	器具間隔最大限		2.5	86	80	74	69	83	77	71	67	76	71	66	63	69	65	62	59	52
	横方向 (A)	縦方向 (B)	3.0	89	83	78	73	85	80	75	71	78	74	70	66	72	68	65	62	55
H m	1.31H m	1.31H m	4.0	92	87	83	79	89	84	80	77	81	78	75	72	75	72	69	67	59
			5.0	94	90	87	83	91	87	84	81	83	81	78	75	77	74	72	70	62
			7.0	97	94	91	88	93	90	88	85	86	84	82	80	79	77	76	74	66
			10.0	99	96	94	92	95	93	91	89	88	86	85	83	81	80	78	77	69

