

# 屋内照明器具特性

|         |                     |            |
|---------|---------------------|------------|
| 品番 (品名) | XND9987SWZ          |            |
| 光源      | LED4000_80_12355 ×1 | 12355.0 lm |
| 管理番号    | K0188512(0)DB1      |            |
| BZ分類    | BZ1                 |            |

| 器具効率   | 100%    | 天井              | 80%  |               |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0% |    |  |  |  |
|--------|---------|-----------------|------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|--|--|--|
|        |         |                 | 壁    | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 0% |  |  |  |
| 上方光束   | 0%      | 反射率             | 床    | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0% |  |  |  |
| 下方光束   | 100%    |                 | 室指数  | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  |  |  |
| 保守率    | 良       | 0.76            | 0.6  | 72            | 64  | 58  | 54  | 71  | 63  | 58  | 54  | 70  | 62  | 57  | 54  | 68  | 62  | 57 | 54 | 52 |  |  |  |
|        | 中       | 0.72            | 0.8  | 82            | 75  | 69  | 66  | 81  | 74  | 69  | 66  | 79  | 73  | 69  | 65  | 77  | 72  | 68 | 65 | 64 |  |  |  |
|        | 否       | 0.64            | 1.0  | 88            | 81  | 77  | 73  | 87  | 81  | 76  | 73  | 85  | 79  | 76  | 72  | 83  | 78  | 75 | 72 | 71 |  |  |  |
|        |         |                 | 1.25 | 92            | 87  | 82  | 79  | 91  | 86  | 82  | 79  | 89  | 85  | 81  | 78  | 87  | 83  | 80 | 78 | 76 |  |  |  |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5  | 95            | 90  | 86  | 83  | 94  | 89  | 86  | 83  | 92  | 88  | 85  | 82  | 90  | 87  | 84 | 81 | 80 |  |  |  |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0  | 99            | 95  | 91  | 89  | 97  | 94  | 91  | 88  | 95  | 92  | 90  | 87  | 93  | 91  | 88 | 86 | 85 |  |  |  |
| 取付高さ   | 器具間隔最大限 |                 | 2.5  | 101           | 97  | 95  | 92  | 100 | 96  | 94  | 92  | 97  | 95  | 93  | 91  | 95  | 93  | 91 | 90 | 88 |  |  |  |
|        | 横方向 (A) | 縦方向 (B)         | 3.0  | 102           | 99  | 97  | 95  | 101 | 98  | 96  | 94  | 99  | 96  | 95  | 93  | 97  | 95  | 93 | 92 | 90 |  |  |  |
| Hm     | 1.36Hm  | 1.36Hm          | 4.0  | 104           | 102 | 100 | 98  | 103 | 101 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97  | 96 | 94 | 92 |  |  |  |
|        |         |                 | 5.0  | 105           | 103 | 101 | 100 | 104 | 102 | 100 | 99  | 101 | 100 | 99  | 97  | 99  | 98  | 97 | 96 | 94 |  |  |  |
|        |         |                 | 7.0  | 106           | 105 | 103 | 102 | 105 | 103 | 102 | 101 | 102 | 101 | 100 | 100 | 100 | 99  | 99 | 98 | 95 |  |  |  |
|        |         |                 | 10.0 | 107           | 106 | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 99 | 97 | 97 |  |  |  |

