

屋内照明器具特性

品番 (品名)	HH- CD0895AE	
光源	LED6200_70_3800 x1	3800.0 lm
管理番号	K0163083(0)D 1	
BZ分類	BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		29%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		71%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	50	37	29	24	47	35	28	23	41	32	26	21	37	29	23	19	16	
	中	0.6	0.8	59	47	38	32	55	44	37	31	49	40	34	29	44	36	31	27	22	
	否	0.56	1.0	65	54	45	39	61	51	43	38	55	46	40	35	48	42	36	32	27	
			1.25	71	60	52	46	67	57	50	44	60	52	46	41	53	47	42	38	31	
下方投影面積	cm ²		1.5	75	65	58	52	71	62	55	50	63	56	50	46	56	51	46	42	35	
	等価発光面積		cm ²	2.0	81	72	65	60	76	69	63	58	68	62	57	53	61	56	52	49	41
取付高さ	器具間隔最大限		2.5	84	77	71	66	80	73	68	63	72	67	62	58	64	60	57	53	45	
	横方向 (A)	縦方向 (B)	3.0	87	80	75	70	83	77	72	67	74	70	66	62	67	63	60	57	48	
H _m	1.35H _m	1.35H _m	4.0	90	85	80	76	86	81	77	73	78	74	71	67	70	67	64	62	53	
			5.0	92	88	84	80	88	84	81	77	80	77	74	71	72	69	67	65	56	
			7.0	95	92	88	86	91	88	85	82	82	80	78	75	74	73	71	69	59	
			10.0	97	94	92	90	93	90	88	86	84	83	81	79	76	75	74	72	62	

