

屋内照明器具特性

品番 (品名)	HH- CD1020AZ														
光源	LED6200_70_4899 x1 4899.0 lm														
管理番号	K0155145(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	8%	室指数	照明率 (X0.01) ZCM																		
下方光束	92%																				
保守率	良 0.63 中 0.6 否 0.56	0.6	55	43	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25		
		0.8	64	53	45	39	62	52	44	39	59	50	43	38	55	48	42	37	34		
		1.0	71	60	52	46	69	59	51	46	65	56	50	45	61	54	48	44	41		
		1.25	77	67	59	53	74	65	58	53	70	63	56	52	66	60	55	50	47		
下方投影面積	c m ²	1.5	81	72	65	59	78	70	63	58	74	67	61	57	70	64	59	55	52		
		2.0	86	79	72	67	84	77	71	66	80	74	69	64	75	71	66	63	59		
取付高さ	器具間隔最大限		2.5	90	83	77	73	87	81	76	72	83	78	73	70	79	75	71	68	64	
	横方向 (A)	縦方向 (B)	3.0	92	86	81	77	90	85	80	76	86	81	77	74	81	78	74	71	67	
H m	1.24 H m	1.24 H m	4.0	95	91	86	83	93	89	85	81	89	85	82	79	85	82	79	76	72	
			5.0	97	93	90	86	95	91	88	85	91	88	85	82	87	84	82	80	75	
			7.0	100	97	94	91	97	95	92	90	93	91	89	87	89	87	86	84	79	
			10.0	101	99	97	95	99	97	95	93	95	93	92	90	91	90	88	87	82	

