

屋内照明器具特性	
品番 (品名)	L G B 5 0 2 1 4
光源	LED2700_70_1600 ×1 1600.0 l m
管理番号	K0157927 (0) D 1
B Z 分類	B Z 5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %			
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
					床	10 %				10 %				10 %				10 %				0 %			
上方光束		3 %		室指数	照明率 (X0.01)																			Z C M	
下方光束		97 %																							
保守率		良 中 否	0.69	0.6	56	44	36	31	55	43	36	30	52	42	35	30	50	41	34	30	28				
			0.67	0.8	66	54	46	41	64	54	46	41	61	52	45	40	58	50	44	40	37				
			0.63	1.0	73	62	54	48	71	61	53	48	67	59	52	47	64	57	51	47	44				
				1.25	79	69	61	56	77	68	61	55	73	65	59	54	70	63	58	54	51				
下方投影面積		cm ²		1.5	83	74	67	61	81	72	66	61	77	70	64	60	74	68	63	59	56				
等価発光面積		cm ²		2.0	88	81	75	69	86	79	74	69	83	77	72	68	79	74	70	67	63				
取付 高さ	器具間隔最大限			2.5	92	85	80	75	90	84	79	74	86	81	77	73	83	79	75	72	69				
	横方向 (A)		縦方向 (B)	3.0	94	89	84	79	92	87	83	79	89	84	81	77	86	82	79	76	72				
1.5m	1.97 m	2.23 m		4.0	97	93	89	85	96	91	88	84	92	89	85	83	89	86	83	81	77				
2	2.59	2.74		5.0	99	96	92	89	98	94	91	88	94	91	89	86	91	89	86	84	81				
2.5	3.21	3.3		7.0	102	99	96	94	100	97	95	93	97	94	92	90	94	92	90	88	85				
3	3.84	3.86		10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	92	88				

