

# 屋内照明器具特性

品番 (品名)	HH- CD1 2 1 0 DS									
光源	LED6200_70_5499 x1 5499.0 lm									
管理番号	K0161618(0)D 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
		床	10 %				10 %				10 %				10 %				0 %			
上方光束	8 %																					
下方光束	92 %																					
室指数	照明率 ( X0.01 )																ZCM					
保守率	良	0.63	0.6	0.5	0.4	0.3	0.2	0.1	0.05	0.02	0.01	0.005	0.002	0.001	0.0005	0.0002	0.0001	0.00005	0.00002	0.00001		
	中	0.6	0.6	0.5	0.4	0.3	0.2	0.1	0.05	0.02	0.01	0.005	0.002	0.001	0.0005	0.0002	0.0001	0.00005	0.00002	0.00001		
	否	0.56	0.5	0.4	0.3	0.2	0.1	0.05	0.02	0.01	0.005	0.002	0.001	0.0005	0.0002	0.0001	0.00005	0.00002	0.00001	0.000005		
	0.56	0.5	0.4	0.3	0.2	0.1	0.05	0.02	0.01	0.005	0.002	0.001	0.0005	0.0002	0.0001	0.00005	0.00002	0.00001	0.000005	0.000002		
下方投影面積			cm <sup>2</sup>																			
			cm <sup>2</sup>																			
取付高さ	器具間隔最大限																					
	横方向 (A)	縦方向 (B)																				
Hm	1.25Hm	1.25Hm	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0	22.0	
			100	98	96	94	92	90	88	86	84	82	80	78	76	74	72	70	68	66	64	
			100	97	94	92	90	88	86	84	82	80	78	76	74	72	70	68	66	64	62	60
			100	97	94	92	90	88	86	84	82	80	78	76	74	72	70	68	66	64	62	60
			100	97	94	92	90	88	86	84	82	80	78	76	74	72	70	68	66	64	62	60

