

# 屋内照明器具特性

品番 (品名)	HH- CD1 2 1 9 AH									
光源	LED6200_70_5050 x1 5050.0 lm									
管理番号	K0150028(0)D 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	3 %																			
下方光束	97 %																			
室指数	照明率 ( X0.01 )																		ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	56	44	36	31	55	44	36	31	52	42	35	31	50	41	35	30	28	
		0.8	66	55	47	41	65	54	47	41	62	52	46	41	59	51	45	40	38	
		1.0	73	62	54	49	71	61	54	48	68	59	53	48	65	57	52	47	45	
		1.25	79	69	62	56	77	68	61	56	73	66	60	55	70	64	58	54	51	
下方投影面積	c m <sup>2</sup>	1.5	83	74	67	62	81	73	66	61	77	70	65	60	74	68	63	59	56	
		2.0	88	81	75	70	86	80	74	69	83	77	72	68	79	75	70	67	64	
取付高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	75	86	81	77	73	83	79	75	72	69
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	83	79	89	84	81	77	85	82	79	76	72
H m	1.24 H m	1.24 H m	4.0	97	93	89	85	96	91	88	84	92	89	85	83	89	86	83	81	77
			5.0	99	96	92	89	98	94	91	88	94	91	89	86	91	88	86	84	81
			7.0	102	99	96	94	100	97	95	93	96	94	92	90	93	91	90	88	84
			10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	91	88

