

# 屋内照明器具特性

品番 (品名)	HH- CD1 2 2 0 AZ														
光源	LED6200_70_5499 x1 5499.0 lm														
管理番号	K0155145 ( 0 ) DB 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	8 %	室指数	照明率 ( X0.01 )															ZCM			
下方光束	92 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	5.5	4.3	3.5	2.9	5.3	4.2	3.4	2.9	5.0	4.0	3.3	2.8	4.7	3.8	3.2	2.8	2.5		
		0.8	6.4	5.3	4.5	3.9	6.2	5.2	4.4	3.9	5.9	5.0	4.3	3.8	5.5	4.8	4.2	3.7	3.4		
		1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.6	6.5	5.6	5.0	4.5	6.1	5.4	4.8	4.4	4.1		
		1.25	7.7	6.7	5.9	5.3	7.4	6.5	5.8	5.3	7.0	6.3	5.6	5.2	6.6	6.0	5.5	5.0	4.7		
下方投影面積	c m <sup>2</sup>	1.5	8.1	7.2	6.5	5.9	7.8	7.0	6.3	5.8	7.4	6.7	6.1	5.7	7.0	6.4	5.9	5.5	5.2		
		2.0	8.6	7.9	7.2	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.4	7.5	7.1	6.6	6.3	5.9		
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.7	7.3	8.7	8.1	7.6	7.2	8.3	7.8	7.3	7.0	7.9	7.5	7.1	6.8	6.4	
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.7	9.0	8.5	8.0	7.6	8.6	8.1	7.7	7.4	8.1	7.8	7.4	7.1	6.7	
H m	1.24 H m	1.24 H m	4.0	9.5	9.1	8.6	8.3	9.3	8.9	8.5	8.1	8.9	8.5	8.2	7.9	8.5	8.2	7.9	7.6	7.2	
			5.0	9.7	9.3	9.0	8.6	9.5	9.1	8.8	8.5	9.1	8.8	8.5	8.2	8.7	8.4	8.2	8.0	7.5	
			7.0	10.0	9.7	9.4	9.1	9.7	9.5	9.2	9.0	9.3	9.1	8.9	8.7	8.9	8.7	8.6	8.4	7.9	
			10.0	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.5	9.3	9.2	9.0	9.1	9.0	8.8	8.7	8.2	

