

屋内照明器具特性

品番 (品名)	HH- CD1 2 3 2 A														
光源	LED6200_70_5150 x1 5150.0 lm														
管理番号	K0161976(0)D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	3 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	97 %		室指数	照明率 (X0.01) ZCM																
保守率	良	0.63	0.6	55	43	35	29	54	42	34	29	51	40	34	29	48	39	33	28	26
	中	0.6	0.8	65	53	45	39	63	52	45	39	60	51	44	39	57	49	43	38	36
	否	0.56	1.0	72	61	53	47	70	60	52	46	67	58	51	46	63	56	50	45	43
			1.25	78	68	60	54	76	67	59	54	72	64	58	53	69	62	57	52	50
下方投影面積			1.5	82	73	66	60	80	72	65	59	76	69	63	59	73	67	62	58	55
等価発光面積			2.0	88	80	74	68	86	79	73	68	82	76	71	67	79	74	69	66	62
取付高さ	器具間隔最大限		2.5	91	85	79	74	89	83	78	74	86	81	76	72	82	78	74	71	68
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	76	85	81	78	75	72
Hm	1.35Hm	1.35Hm	4.0	97	92	88	85	95	91	87	84	92	88	85	82	89	86	83	80	77
			5.0	99	95	92	88	97	94	90	87	94	91	88	86	91	88	86	84	80
			7.0	101	98	96	93	100	97	94	92	96	94	92	90	93	91	90	88	84
			10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	91	88

