

# 屋内照明器具特性

品番 (品名)	HH- CD1 2 3 4 A														
光源	LED6200_70_5499 x1 5499.0 lm														
管理番号	K0161951(0)D 1														
BZ分類	BZ6/0.9/BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
		床	10 %				10 %				10 %				10 %				0 %			
上方光束	6 %	室指数																				
下方光束	94 %	照明率 ( X0.01 )																				
		ZCM																				
保守率	良 中 否	0.63	0.6	0.56	0.6	53	40	32	26	51	39	31	26	48	38	30	25	45	36	30	25	23
		0.6	0.8	63	51	42	36	61	49	42	36	57	47	40	35	54	46	39	34	32		
		0.56	1.0	69	58	50	43	67	57	49	43	64	54	47	42	60	52	46	41	38		
			1.25	76	65	57	51	73	64	56	50	69	61	54	49	66	59	53	48	45		
下方投影面積	c m <sup>2</sup>	1.5	80	70	63	57	78	69	62	56	73	66	60	55	70	63	58	53	50			
		2.0	86	77	71	65	83	76	70	64	79	73	67	63	75	70	65	61	58			
取付高さ	器具間隔最大限		2.5	89	82	76	71	87	81	75	70	83	77	73	68	79	74	70	67	63		
	横方向 (A)	縦方向 (B)	3.0	92	86	80	76	90	84	79	75	86	81	76	73	82	78	74	71	67		
H m	1.47 H m	1.47 H m	4.0	95	90	86	82	93	89	84	81	89	85	82	78	85	82	79	76	72		
			5.0	98	93	89	86	95	91	88	85	91	88	85	82	87	85	82	80	76		
			7.0	100	97	94	91	98	95	92	90	94	91	89	87	90	88	86	84	80		
			10.0	102	100	97	95	100	98	96	94	96	94	92	91	92	91	89	88	83		

