

屋内照明器具特性

品番 (品名)	HH-CE0828DH									
光源	LED6500_70_4299 x1 4299.0lm									
管理番号	K0161618(0)D1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	8%	室指数	照明率 (X0.01)																ZCM	
下方光束	92%																			
保守率	良 中 否 0.63 0.6 0.56	0.6	5.5	4.3	3.5	2.9	5.3	4.2	3.4	2.9	5.0	4.0	3.3	2.9	4.7	3.8	3.2	2.8	2.6	
		0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.4	3.9	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.7	3.4	
		1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.2	4.6	6.5	5.6	5.0	4.5	6.1	5.4	4.8	4.4	4.1	
		1.25	7.7	6.7	6.0	5.4	7.5	6.6	5.9	5.3	7.0	6.3	5.7	5.2	6.7	6.0	5.5	5.0	4.7	
下方投影面積	c m ²	1.5	8.1	7.2	6.5	5.9	7.9	7.0	6.4	5.8	7.4	6.7	6.2	5.7	7.0	6.4	5.9	5.5	5.2	
		2.0	8.7	7.9	7.3	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.5	7.6	7.1	6.6	6.3	5.9	
取付高さ	器具間隔最大限		2.5	9.0	8.3	7.8	7.3	8.8	8.2	7.6	7.2	8.3	7.8	7.4	7.0	7.9	7.5	7.1	6.8	6.4
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.7	9.0	8.5	8.0	7.6	8.6	8.1	7.7	7.4	8.2	7.8	7.4	7.1	6.7
H m	1.25 H m	1.25 H m	4.0	9.6	9.1	8.7	8.3	9.3	8.9	8.5	8.2	8.9	8.5	8.2	7.9	8.5	8.2	7.9	7.7	7.2
			5.0	9.8	9.4	9.0	8.7	9.5	9.2	8.8	8.5	9.1	8.8	8.5	8.3	8.7	8.4	8.2	8.0	7.5
			7.0	10.0	9.7	9.4	9.2	9.8	9.5	9.2	9.0	9.3	9.1	8.9	8.7	8.9	8.7	8.6	8.4	7.9
			10.0	10.2	10.0	9.7	9.5	10.0	9.8	9.6	9.4	9.5	9.4	9.2	9.0	9.1	9.0	8.9	8.7	8.2

