

屋内照明器具特性

品番 (品名)	HH-CE0832A														
光源	LED6200_70_4050 x1 4050.0 lm														
管理番号	K0168482(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	3%	反射率	床	10%				10%				10%				10%				0%
下方光束	97%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否 0.63 0.6 0.56	0.6	55	43	35	29	54	42	34	29	51	40	34	29	48	39	33	28	26	
		0.8	65	53	45	39	63	52	45	39	60	51	44	39	57	49	43	38	36	
		1.0	72	61	53	47	70	60	52	47	67	58	51	46	63	56	50	45	43	
		1.25	78	68	60	54	76	67	60	54	72	64	58	53	69	62	57	52	50	
下方投影面積	c m ²	1.5	82	73	66	60	80	72	65	60	76	69	63	59	73	67	62	58	55	
		2.0	88	80	74	69	86	79	73	68	82	76	71	67	79	74	69	66	63	
取付高さ	器具間隔最大限		2.5	91	85	79	75	89	83	78	74	86	81	76	72	82	78	74	71	68
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	77	85	81	78	75	72
H m	1.35 H m	1.35 H m	4.0	97	93	89	85	95	91	87	84	92	88	85	82	88	86	83	80	77
			5.0	99	95	92	89	97	94	91	88	94	91	88	86	91	88	86	84	80
			7.0	101	99	96	93	100	97	95	92	96	94	92	90	93	91	90	88	84
			10.0	103	101	99	97	102	100	98	96	98	97	95	94	95	94	93	91	88

