

# 屋内照明器具特性

|         |                   |  |  |  |  |          |  |  |  |  |
|---------|-------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | NNQ35417K         |  |  |  |  |          |  |  |  |  |
| 光源      | LED3000_85_770 x1 |  |  |  |  | 770.0 lm |  |  |  |  |
| 管理番号    | K0190146(1)DR1    |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ1               |  |  |  |  |          |  |  |  |  |

| 器具効率   | 100%             | 天井      | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0%  |    |
|--------|------------------|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|----|
|        |                  |         | 壁                | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10  | 0% |
| 上方光束   | 0%               | 床       | 10%              |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0%  |    |
| 下方光束   | 100%             | 室指数     | 照明率 ( X0.01 )    |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    | ZCM |    |
| 保守率    | 良                | 0.81    | 0.6              | 72  | 63  | 58  | 54  | 71  | 63  | 57  | 54  | 69  | 62  | 57  | 53  | 68  | 61 | 57 | 53  | 52 |
|        | 中                | 0.77    | 0.8              | 81  | 74  | 68  | 65  | 80  | 73  | 68  | 65  | 78  | 72  | 68  | 64  | 76  | 71 | 67 | 64  | 63 |
|        | 否                | 0.68    | 1.0              | 87  | 80  | 75  | 72  | 86  | 80  | 75  | 72  | 84  | 78  | 74  | 71  | 82  | 77 | 74 | 71  | 69 |
|        |                  |         | 1.25             | 91  | 86  | 81  | 78  | 90  | 85  | 81  | 77  | 88  | 83  | 80  | 77  | 86  | 82 | 79 | 76  | 75 |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 94  | 89  | 85  | 82  | 93  | 88  | 84  | 81  | 91  | 87  | 83  | 81  | 89  | 85 | 83 | 80  | 78 |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0 | 98  | 94  | 90  | 87  | 97  | 93  | 90  | 87  | 94  | 91  | 88  | 86  | 92 | 90 | 87  | 85 |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 100 | 96  | 93  | 91  | 99  | 95  | 93  | 90  | 96  | 94  | 91  | 89  | 94  | 92 | 90 | 88  | 86 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 101 | 98  | 96  | 93  | 100 | 97  | 95  | 93  | 98  | 96  | 93  | 92  | 96  | 94 | 92 | 91  | 88 |
| H m    | 1.21H m          | 1.21H m | 4.0              | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 97  | 96 | 95 | 93  | 91 |
|        |                  |         | 5.0              | 104 | 102 | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 97 | 96 | 95  | 93 |
|        |                  |         | 7.0              | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 100 | 99 | 98 | 97  | 95 |
|        |                  |         | 10.0             | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 99 | 99 | 99  | 96 |

