

屋内照明器具特性

品番 (品名)	XSZR3020L		
光源	LLD3420LCB1 ×1	700.0 1m	
管理番号	K0192056(0)DB1		
BZ分類	BZ1		

器具効率	86%	天井	80%				70%				50%				30%				0%					
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
下方光束	86%	床	10%				10%				10%				10%				0%					
室指数			照明率 (X0.01)																ZCM					
保守率	良	0.63	0.6	0.6	69	63	60	57	69	63	60	57	67	63	59	57	66	62	59	57	56			
	中	0.6	0.8	75	70	66	64	74	70	66	64	73	69	66	63	72	68	65	63	62				
	否	0.56	1.0	79	74	71	68	78	74	70	68	76	73	70	68	75	72	69	67	66				
下方投影面積	等価発光面積	cm ²	cm ²	1.25	82	78	75	72	81	77	74	72	79	76	74	72	78	75	73	71	70			
				1.5	84	80	77	75	83	79	77	75	81	78	76	74	80	77	75	74	72			
取付高さ	器具間隔最大限		Hm	0.54Hm	Hm	0.54Hm	2.5	88	85	83	81	87	84	83	81	85	83	81	80	83	82	80	79	77
	横方向 (A)	縦方向 (B)					3.0	89	87	85	83	88	86	84	83	86	84	83	82	84	83	82	81	79
Hm						4.0	90	88	87	85	89	87	86	85	87	86	85	84	85	84	83	83	81	
						5.0	91	89	88	87	90	88	87	86	88	87	86	85	86	85	84	84	82	
						7.0	91	90	90	89	90	90	89	88	89	88	87	86	87	86	86	86	85	83
						10.0	92	91	91	90	91	90	90	89	89	89	88	88	87	87	86	84		

