

屋内照明器具特性	
品番 (品名)	FYY43005J (JYOUJI)
光源	LDA7N-D-G/S/Z6 ×1 810.0 lm
管理番号	K0172080 (0) DR1
BZ分類	BZ9/0.7/BZ8

器具効率		9 1 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		4 5 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		4 6 %																							
保守率		良 中 否	0 . 6 3	0 . 6	4 1	3 0	2 3	1 8	3 8	2 7	2 1	1 6	3 1	2 3	1 7	1 4	2 5	1 9	1 4	1 1	6				
			0 . 6	0 . 8	4 9	3 8	3 0	2 5	4 5	3 5	2 8	2 3	3 7	2 9	2 3	1 9	2 9	2 4	1 9	1 6	1 0				
			0 . 5 6	1 . 0	5 4	4 4	3 6	3 0	5 0	4 0	3 3	2 8	4 1	3 3	2 8	2 4	3 3	2 7	2 3	1 9	1 2				
				1 . 2 5	5 9	4 9	4 2	3 6	5 4	4 5	3 9	3 3	4 5	3 8	3 3	2 8	3 6	3 1	2 7	2 3	1 5				
下方投影面積		c m ²	1 . 5	6 3	5 4	4 6	4 1	5 8	4 9	4 3	3 8	4 8	4 1	3 6	3 2	3 9	3 4	3 0	2 6	1 7					
等価発光面積			c m ²	2 . 0	6 8	6 0	5 3	4 8	6 2	5 5	4 9	4 4	5 2	4 6	4 2	3 8	4 2	3 8	3 4	3 1	2 1				
取付 高さ	器具間隔最大限		2 . 5	7 1	6 4	5 8	5 3	6 6	5 9	5 4	4 9	5 5	5 0	4 6	4 2	4 5	4 1	3 8	3 5	2 3					
	横方向 (A) 縦方向 (B)		3 . 0	7 4	6 7	6 2	5 7	6 8	6 2	5 7	5 3	5 7	5 2	4 9	4 5	4 7	4 3	4 0	3 8	2 6					
H m	1 . 5 4 H m	1 . 8 8 H m	4 . 0	7 7	7 2	6 7	6 3	7 1	6 6	6 2	5 8	6 0	5 6	5 3	5 0	4 9	4 6	4 4	4 1	2 9					
			5 . 0	7 9	7 4	7 0	6 7	7 3	6 9	6 5	6 2	6 2	5 8	5 6	5 3	5 1	4 8	4 6	4 4	3 1					
			7 . 0	8 1	7 8	7 5	7 1	7 5	7 2	6 9	6 7	6 4	6 1	5 9	5 7	5 3	5 1	4 9	4 8	3 4					
			1 0 . 0	8 3	8 1	7 8	7 6	7 7	7 5	7 3	7 0	6 6	6 4	6 2	6 0	5 5	5 3	5 2	5 1	3 6					

