

屋内照明器具特性

| | | | | | | | | | | | | | |
|---------|--------------------------------------|---------|------|---|---|----------|---|---|---|---|---|---|--|
| 品番 (品名) | YYY66503K | | | | | | | | | | | | |
| 光源 | LDA7L-G-E17/K60E/S/W/2 ×1 | | | | | 760.0 lm | | | | | | | |
| 管理番号 | K0188311(0)DB1 | | | | | | | | | | | | |
| BZ分類 | BZ10/0.9/BZ9/1.4/BZ8/2.8/BZ7/8.5/BZ6 | | | | | | | | | | | | |
| 器具効率 | 8% | 反射率 | 天井 | % | | % | | % | | % | | % | |
| | 上方光束 | | 1% | 壁 | % | | % | | % | | % | | |
| | 下方光束 | | 7% | 床 | % | | % | | % | | % | | |
| 室指数 | 照明率 (X0.01) ZCM | | | | | | | | | | | | |
| 保守率 | 良 | 0.63 | 0.6 | | | | | | | | | | |
| | 中 | 0.6 | 0.8 | | | | | | | | | | |
| | 否 | 0.56 | 1.0 | | | | | | | | | | |
| 下方投影面積 | cm ² | | 1.25 | | | | | | | | | | |
| 等価発光面積 | cm ² | | 1.5 | | | | | | | | | | |
| 取付高さ | 器具間隔最大限 | | 2.5 | | | | | | | | | | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | | | | | | | | | | |
| Hm | 0.00Hm | 0.20Hm | 4.0 | | | | | | | | | | |
| | | | 5.0 | | | | | | | | | | |
| | | | 7.0 | | | | | | | | | | |
| | | | 10.0 | | | | | | | | | | |

