

# 屋内照明器具特性

品番 (品名)	FYY46010														
光源	LDL40S.N/14/26(2600A) ×1 2600.0 1m														
管理番号	K0124841(2)DB1														
BZ分類	BZ5/3.5/BZ6														

器具効率	79%	天井	80%				70%				50%				30%				0%		
	上方光束		37%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		42%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.81	0.6	3.9	3.0	2.4	2.0	3.6	2.8	2.3	1.9	3.1	2.4	2.0	1.7	2.6	2.1	1.7	1.5	1.1	
	中	0.77	0.8	4.6	3.7	3.1	2.7	4.2	3.5	2.9	2.5	3.6	3.0	2.6	2.2	3.0	2.6	2.2	2.0	1.5	
	否	0.68	1.0	5.1	4.2	3.6	3.2	4.7	4.0	3.4	3.0	4.0	3.4	3.0	2.7	3.3	2.9	2.6	2.3	1.7	
			0.68	1.25	5.5	4.7	4.2	3.7	5.1	4.4	3.9	3.5	4.3	3.8	3.4	3.1	3.6	3.2	2.9	2.7	2.0
下方投影面積			cm <sup>2</sup>																		
等価発光面積			cm <sup>2</sup>																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
1.5m	2.08m	2.19m	4.0	6.9	6.5	6.2	5.9	6.4	6.1	5.8	5.5	5.5	5.3	5.0	4.7	4.5	4.5	4.2	4.0	3.9	2.9
2	2.74	2.78	5.0	7.1	6.7	6.5	6.2	6.6	6.3	6.0	5.8	5.7	5.4	5.3	5.1	4.8	4.6	4.5	4.4	3.3	
2.5	3.41	3.39	7.0	7.2	7.0	6.8	6.6	6.7	6.5	6.3	6.2	5.8	5.7	5.5	5.4	4.9	4.8	4.7	4.6	3.5	
3	4.07	4.01	10.0	7.4	7.2	7.0	6.9	6.9	6.7	6.6	6.4	5.9	5.8	5.7	5.6	5.1	5.0	4.9	4.8	3.6	

