

# 屋内照明器具特性

品番 (品名)	HH- CF0835AJ														
光源	LED6200_70_4299 x1 4299.0 lm														
管理番号	K0168476(0)DB1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	7 %	室指数	照明率 ( X0.01 )																			ZCM
下方光束	93 %																					
保守率	良 中 否	0.63	0.6	0.56	0.6	54	42	34	28	53	41	33	28	49	39	32	27	47	38	32	27	25
		0.6	0.8	64	52	44	38	62	51	44	38	59	49	42	37	55	47	41	36	34		
		0.56	1.0	71	60	52	46	69	58	51	45	65	56	49	44	61	54	48	43	40		
			1.25	77	67	59	53	75	65	58	53	70	63	56	51	67	60	55	50	47		
下方投影面積	c m <sup>2</sup>	1.5	81	72	65	59	79	70	63	58	74	67	61	57	71	65	60	55	52			
		2.0	87	79	73	67	84	77	71	66	80	74	69	65	76	71	67	63	59			
取付高さ	器具間隔最大限		2.5	90	84	78	73	88	82	77	72	84	79	74	70	80	75	72	68	64		
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	85	80	76	86	82	78	74	82	79	75	72	68		
H m	1.34 H m	1.34 H m	4.0	96	91	87	83	94	90	86	82	90	86	83	80	86	83	80	77	73		
			5.0	98	94	91	87	96	92	89	86	92	89	86	83	88	85	83	81	76		
			7.0	100	97	95	92	98	96	93	91	94	92	90	88	90	88	87	85	80		
			10.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	90	88	84		

