

|          |                               |
|----------|-------------------------------|
| 屋内照明器具特性 |                               |
| 品番 (品名)  | NWCF59418                     |
| 光源       | LED3500_70_430 x1 430.0 lm    |
| 管理番号     | K0190689(0)DR1                |
| BZ分類     | BZ10/2.8/BZ9/3.5/BZ10/4.5/BZ9 |

|                |                    |                    |               |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    |     |    |
|----------------|--------------------|--------------------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率           | 100%               | 天井                 | 80%           |    |    |    | 70% |    |    |    | 50% |    |    |    | 30% |    |    |    | 0%  |    |
|                |                    | 壁                  | 70            | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 70  | 50 | 30 | 10 | 0%  |    |
| 上方光束           | 50%                | 床                  | 10%           |    |    |    | 10% |    |    |    | 10% |    |    |    | 10% |    |    |    | 0%  |    |
| 下方光束           | 50%                | 室指数                | 照明率 ( X0.01 ) |    |    |    |     |    |    |    |     |    |    |    |     |    |    |    | ZCM |    |
| 保守率            | 良                  | 0.63               | 0.6           | 43 | 30 | 22 | 17  | 39 | 28 | 20 | 15  | 32 | 23 | 17 | 12  | 25 | 18 | 13 | 9   | 4  |
|                | 中                  | 0.6                | 0.8           | 51 | 39 | 30 | 24  | 47 | 35 | 28 | 22  | 38 | 29 | 23 | 18  | 30 | 23 | 18 | 14  | 7  |
|                | 否                  | 0.56               | 1.0           | 57 | 45 | 36 | 30  | 52 | 41 | 33 | 27  | 42 | 34 | 27 | 22  | 34 | 27 | 22 | 18  | 10 |
|                |                    |                    | 1.25          | 63 | 51 | 43 | 36  | 57 | 47 | 39 | 33  | 47 | 39 | 32 | 27  | 37 | 31 | 26 | 22  | 13 |
| 下方投影面積         |                    | cm <sup>2</sup>    | 1.5           | 67 | 56 | 48 | 41  | 61 | 51 | 44 | 38  | 50 | 42 | 36 | 31  | 40 | 34 | 29 | 25  | 15 |
| 等価発光面積         |                    | cm <sup>2</sup>    | 2.0           | 73 | 63 | 55 | 49  | 66 | 58 | 51 | 45  | 55 | 48 | 43 | 38  | 44 | 39 | 35 | 31  | 19 |
| 取付高さ           | 器具間隔最大限            |                    | 2.5           | 76 | 68 | 61 | 55  | 70 | 62 | 56 | 51  | 58 | 52 | 47 | 43  | 47 | 42 | 38 | 35  | 22 |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0           | 79 | 72 | 65 | 59  | 73 | 66 | 60 | 55  | 60 | 55 | 50 | 46  | 49 | 45 | 41 | 38  | 25 |
| H <sub>m</sub> | 0.00H <sub>m</sub> | 1.73H <sub>m</sub> | 4.0           | 83 | 76 | 71 | 66  | 76 | 71 | 65 | 61  | 64 | 59 | 55 | 52  | 52 | 49 | 45 | 43  | 28 |
|                |                    |                    | 5.0           | 85 | 80 | 75 | 70  | 79 | 74 | 69 | 65  | 66 | 62 | 59 | 55  | 54 | 51 | 48 | 46  | 31 |
|                |                    |                    | 7.0           | 88 | 84 | 80 | 76  | 81 | 78 | 74 | 71  | 69 | 66 | 63 | 60  | 57 | 54 | 52 | 50  | 35 |
|                |                    |                    | 10.0          | 90 | 87 | 84 | 81  | 84 | 81 | 78 | 75  | 71 | 69 | 66 | 64  | 59 | 57 | 55 | 54  | 38 |

