

# 屋内照明器具特性

品番 (品名)	NNQ3 5 4 7 3 K	
光源	LED2700_85_5690 ×1	5690.0 lm
管理番号	K0186393 (0) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	100 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良 0.81	0.6	89	84	81	79	88	84	81	79	87	83	81	79	86	83	80	78	78	
	中 0.77		0.8	94	90	87	84	93	89	86	84	92	88	86	84	91	88	85	84	83
	否 0.68		1.0	97	93	90	88	96	93	90	88	95	92	89	88	93	91	89	87	86
下方投影面積	cm <sup>2</sup>	1.25	99	96	93	91	98	95	93	91	97	94	92	91	95	93	91	90	89	
		1.5	101	98	95	94	100	97	95	93	98	96	94	93	97	95	93	92	90	
等価発光面積	cm <sup>2</sup>	2.0	103	100	98	97	102	100	98	96	100	98	97	95	98	97	96	94	93	
		2.5	104	102	100	99	103	101	99	98	101	99	98	97	99	98	97	96	94	
取付高さ	器具間隔最大限		3.0	105	103	101	100	104	102	101	99	102	100	99	98	100	99	98	97	95
	横方向 (A)	縦方向 (B)	4.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	99	98	96
Hm	0.81Hm	0.81Hm	5.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	97	
			7.0	107	106	105	104	106	105	104	104	103	102	102	101	101	100	99	98	
			10.0	107	107	106	106	106	105	105	104	104	103	103	102	102	101	101	98	

