

屋内照明器具特性

品番 (品名)	NNQ35779K	
光源	LED3000_85_6970 ×1	6970.0 lm
管理番号	K0186394(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	90	86	83	81	90	86	83	81	89	85	82	81	88	85	82	81	80	
	中	0.77	0.8	95	91	88	86	94	90	88	86	93	90	87	86	92	89	87	85	84	
	否	0.68	1.0	98	94	91	89	97	94	91	89	96	93	91	89	94	92	90	89	87	
下方投影面積 等価発光面積	cm ²	1.25	1.00	97	94	92	99	96	94	92	98	95	93	92	96	94	92	91	90		
		1.5	1.01	98	96	94	100	98	96	94	99	97	95	93	97	95	94	93	91		
		2.0	1.03	101	99	97	102	100	98	97	100	99	97	96	99	97	96	95	93		
取付高さ	器具間隔最大限		2.5	1.04	1.02	1.01	99	1.03	1.01	1.00	99	1.01	1.00	99	1.00	98	97	96	95		
	横方向 (A)	縦方向 (B)	3.0	1.05	1.03	1.02	1.00	1.04	1.02	1.01	1.00	1.02	1.01	1.00	99	1.00	99	98	97		
Hm	0.79Hm	0.79Hm	4.0	1.06	1.04	1.03	1.02	1.05	1.04	1.02	1.01	1.03	1.02	1.01	1.00	1.01	1.00	99	97		
			5.0	1.06	1.05	1.04	1.03	1.05	1.04	1.03	1.03	1.03	1.02	1.02	1.01	1.01	1.01	1.00	1.00		
			7.0	1.07	1.06	1.05	1.05	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.02	1.02	1.01	1.01	1.00		
			10.0	1.07	1.07	1.06	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.02	1.02	1.01	1.01		

