

屋内照明器具特性	
品番 (品名)	FYY26674C
光源	FYY26674Z x1                      2850.0 lm
管理番号	K0125491(6)DB1
BZ分類	BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%																			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																			
		床	10%				10%				10%				10%				0%																			
上方光束	17%	室指数																		照明率 ( X0.01)																		ZCM
下方光束	83%																																					
保守率	良	0.83	0.6	51	39	30	25	49	37	30	24	45	35	28	23	41	33	27	22	19																		
	中	0.81	0.8	60	48	40	34	58	47	39	33	53	44	37	32	49	41	35	30	26																		
	否	0.77	1.0	67	55	47	41	64	53	46	40	59	50	43	38	54	46	41	36	32																		
			1.25	73	62	54	48	70	60	52	46	64	56	49	44	59	52	47	42	37																		
下方投影面積		cm <sup>2</sup>	1.5	77	67	59	53	74	65	58	52	68	60	54	49	62	56	51	47	42																		
	等価発光面積	cm <sup>2</sup>	2.0	83	74	67	62	79	72	65	60	73	67	62	57	68	63	58	54	49																		
取付高さ	器具間隔最大限		2.5	86	79	73	68	83	76	71	66	77	71	67	63	71	67	63	59	53																		
	横方向 (A)	縦方向 (B)	3.0	89	83	77	72	86	80	75	70	80	75	70	67	74	70	66	63	57																		
1.5m	2.04m	2.1m	4.0	93	87	83	78	89	85	80	76	83	79	76	72	77	74	71	68	62																		
2	2.7	2.67	5.0	95	90	86	83	92	87	84	80	85	82	79	76	80	77	74	72	65																		
2.5	3.36	3.25	7.0	97	94	91	88	94	91	88	85	88	86	83	81	82	80	78	76	69																		
3	4.01	3.85	10.0	99	97	94	92	96	94	92	90	90	88	86	85	84	83	81	80	73																		

