

屋内照明器具特性

品番 (品名)	FYY43005J (JYOUJI)									
光源	LDA7N-D-G/S/Z6 ×1					810.0 lm				
管理番号	K0172080(0)DR1									
BZ分類	BZ9/0.7/BZ8									

器具効率	91%	天井	80%				70%				50%				30%				0%		
	上方光束		45%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		46%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	59	49	42	36	54	45	39	33	45	38	33	28	36	31	27	23	15	
	等価発光面積		c m ²	1.5	63	54	46	41	58	49	43	38	48	41	36	32	39	34	30	26	17
取付高さ	器具間隔最大限		2.5	71	64	58	53	66	59	54	49	55	50	46	42	45	41	38	35	23	
	横方向 (A)	縦方向 (B)	3.0	74	67	62	57	68	62	57	53	57	52	49	45	47	43	40	38	26	
H m	1.54 H m	1.88 H m	4.0	77	72	67	63	71	66	62	58	60	56	53	50	49	46	44	41	29	
			5.0	79	74	70	67	73	69	65	62	62	58	56	53	51	48	46	44	31	
			7.0	81	78	75	71	75	72	69	67	64	61	59	57	53	51	49	48	34	
			10.0	83	81	78	76	77	75	73	70	66	64	62	60	55	53	52	51	36	

