

屋内照明器具特性

品番 (品名)	FYY44045J (JYOUJI)	
光源	LDL40S.N/29/38-K ×1	3800.0 lm
管理番号	K0184876(0)DR1	
BZ分類	BZ6/0.7/BZ5/0.9/BZ6	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		50%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		50%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	49	37	30	25	45	35	28	23	38	30	24	20	31	25	21	18	12	
	中	0.77	0.8	57	46	39	33	53	43	36	31	44	37	31	27	37	31	27	23	17	
	否	0.68	1.0	63	53	45	39	58	49	42	37	49	42	36	32	40	35	31	28	20	
			1.25	69	59	52	46	63	55	48	43	53	47	42	37	44	39	35	32	23	
下方投影面積	c m ²		1.5	72	63	56	51	67	59	53	48	56	50	45	41	47	42	38	35	25	
	等価発光面積		c m ²	2.0	78	70	64	59	72	65	59	55	61	55	51	48	50	46	43	40	29
取付高さ	器具間隔最大限		2.5	81	74	69	64	75	69	64	60	63	59	55	52	53	49	46	44	32	
	横方向 (A)	縦方向 (B)	3.0	83	77	72	68	77	72	67	64	65	61	58	55	54	52	49	47	34	
1.5m	2.1m	2.18m	4.0	86	82	77	73	80	76	72	69	68	65	62	59	57	54	52	50	37	
2	2.77	2.75	5.0	88	84	81	77	82	78	75	72	70	67	65	62	58	56	54	53	38	
2.5	3.45	3.34	7.0	91	88	85	82	84	81	79	76	72	70	68	66	60	59	57	56	41	
3	4.12	3.94	10.0	92	90	88	86	86	84	82	80	74	72	71	69	62	61	60	58	43	

