

屋内照明器具特性

品番 (品名)	NTN81042 + NTN81993	
光源	LED3500_70_1130 x1 1130.0 lm	
管理番号	K0163045 (0) DR1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	7 %	反射率	床	10 %				10 %				10 %				10 %				0 %			
下方光束	93 %		室指数	照明率 (X0.01)																			
保守率	良	0.69	0.6	55	42	34	29	53	41	34	28	50	40	33	28	47	38	32	27	25			
	中	0.67	0.8	64	53	44	39	62	51	44	38	59	49	43	37	56	47	41	37	34			
	否	0.63	1.0	71	60	52	46	69	59	51	45	65	56	50	44	61	54	48	43	40			
			1.25	77	67	59	53	75	65	58	53	70	63	56	51	67	60	55	50	47			
下方投影面積	cm ²		1.5	81	72	64	59	79	70	63	58	74	67	61	57	71	64	59	55	52			
等価発光面積	cm ²		2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	67	63	59			
取付高さ	器具間隔最大限		2.5	90	83	78	73	88	82	76	72	84	78	74	70	80	75	71	68	64			
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	90	85	80	76	86	82	77	74	82	78	75	72	68			
1.5m	1.99 m	2.13 m	4.0	96	91	87	83	94	89	85	82	89	86	82	79	85	82	80	77	73			
2	2.63	2.71	5.0	98	94	90	87	96	92	89	86	92	88	86	83	88	85	83	80	76			
2.5	3.27	3.3	7.0	100	97	94	92	98	95	93	90	94	92	89	87	90	88	86	85	80			
3	3.9	3.91	10.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	89	88	83			

