

屋内照明器具特性	
品番 (品名)	LB79902
光源	LDA6L-E17/BH ×1 390.0 l m
管理番号	K0124502 (1) DB 1
BZ分類	BZ3/8.5/BZ2

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %					
	上方光束		0 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
	下方光束		85 %		床	10 %				10 %				10 %				10 %				0 %		
			室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	5.6	4.7	4.1	3.7	5.5	4.6	4.1	3.7	5.3	4.5	4.0	3.7	5.1	4.5	4.0	3.7	3.5				
	中	0.63	0.8	6.4	5.6	5.0	4.6	6.3	5.5	5.0	4.6	6.1	5.4	4.9	4.6	5.9	5.3	4.9	4.6	4.4				
	否	0.56	1.0	6.9	6.2	5.6	5.2	6.8	6.1	5.6	5.2	6.6	6.0	5.5	5.2	6.4	5.9	5.5	5.2	5.0				
			1.25	7.4	6.7	6.2	5.9	7.2	6.6	6.2	5.8	7.0	6.5	6.1	5.8	6.8	6.4	6.0	5.8	5.6				
下方投影面積			1.5	7.7	7.1	6.6	6.3	7.5	7.0	6.6	6.3	7.3	6.9	6.5	6.2	7.1	6.7	6.4	6.2	6.0				
			2.0	8.1	7.6	7.2	6.9	7.9	7.5	7.2	6.9	7.7	7.4	7.1	6.8	7.5	7.2	7.0	6.7	6.5				
取付高さ	器具間隔最大限		2.5	8.3	7.9	7.6	7.3	8.2	7.8	7.5	7.3	8.0	7.7	7.4	7.2	7.8	7.5	7.3	7.1	6.9				
	横方向 (A)	縦方向 (B)	3.0	8.5	8.1	7.8	7.6	8.4	8.0	7.8	7.5	8.1	7.9	7.6	7.4	7.9	7.7	7.5	7.3	7.1				
H m	1.00 H m	1.00 H m	4.0	8.7	8.4	8.2	8.0	8.6	8.3	8.1	7.9	8.3	8.1	8.0	7.8	8.1	8.0	7.8	7.7	7.5				
			5.0	8.8	8.6	8.4	8.2	8.7	8.5	8.3	8.1	8.5	8.3	8.2	8.0	8.3	8.1	8.0	7.9	7.7				
			7.0	8.9	8.8	8.6	8.5	8.8	8.7	8.5	8.4	8.6	8.5	8.4	8.3	8.4	8.3	8.2	8.1	7.9				
			10.0	9.0	8.9	8.8	8.7	8.9	8.8	8.7	8.6	8.7	8.6	8.5	8.5	8.5	8.4	8.4	8.3	8.1				

