

屋内照明器具特性	
品番 (品名)	LGB10443
光源	LED2700_70_340 x1 340.0 lm
管理番号	K0153794(0)DB1
BZ分類	BZ4/1.8/BZ5/6.0/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	12%	床	10%				10%				10%				10%				0%				
下方光束	88%	室指数	照明率 ( X0.01)																				ZCM
保守率	良	0.67	0.6	58	47	40	35	57	46	39	34	53	44	38	34	50	42	37	33	30			
	中	0.63	0.8	68	58	50	45	66	56	49	45	62	54	48	43	58	51	46	42	39			
	否	0.56	1.0	74	64	57	52	72	63	56	51	68	60	54	50	64	57	53	49	45			
			1.25	79	70	63	58	77	68	62	57	72	65	60	56	68	62	58	54	50			
下方投影面積		cm <sup>2</sup>	1.5	82	74	68	62	80	72	66	61	75	69	64	59	71	66	61	58	53			
等価発光面積		cm <sup>2</sup>	2.0	87	79	73	69	84	78	72	67	79	74	69	65	75	70	66	63	58			
取付高さ	器具間隔最大限		2.5	90	83	78	73	87	81	76	72	82	77	73	69	77	73	70	66	62			
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	89	84	79	75	84	79	75	72	79	75	72	69	64			
Hm	1.19Hm	1.19Hm	4.0	94	89	85	81	92	87	83	79	87	83	79	76	82	79	76	73	68			
			5.0	96	92	88	84	94	90	86	83	88	85	82	79	83	81	78	76	70			
			7.0	98	95	92	89	96	93	90	87	91	88	86	83	86	84	82	80	74			
			10.0	100	98	95	93	98	95	93	91	93	91	89	87	88	86	85	83	77			

