

屋内照明器具特性

品番 (品名)	LGB10891														
光源	LED2700_70_342 x1 342.0 lm														
管理番号	K0147052(0)DB1														
BZ分類	BZ4/4.5/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数	照明率 (X0.01)																ZCM		
下方光束	95%																				
保守率	良 中 否	0.67	0.6	60	48	41	36	58	47	41	36	55	46	40	35	53	45	39	35	33	
		0.63	0.8	69	58	51	46	67	57	50	45	64	56	49	45	61	54	48	44	42	
		0.56	1.0	75	65	58	53	73	64	57	52	70	62	56	51	67	60	55	51	48	
			1.25	80	71	65	59	79	70	64	59	75	68	62	58	72	66	61	57	54	
下方投影面積	c m ²	1.5	84	76	70	64	82	75	69	64	79	72	67	63	75	70	65	62	59		
		2.0	89	82	77	72	87	81	76	71	84	78	74	70	80	76	72	69	65		
取付高さ	器具間隔最大限		2.5	93	87	82	77	91	85	81	77	87	82	78	75	83	80	76	73	70	
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	93	88	84	80	89	85	82	78	86	82	79	77	73	
H m	1.21H m	1.21H m	4.0	98	94	90	87	96	92	89	85	92	89	86	83	89	86	84	81	78	
			5.0	100	96	93	90	98	94	92	89	94	91	89	87	91	88	86	84	81	
			7.0	102	99	97	94	100	97	95	93	96	94	92	90	93	91	90	88	84	
			10.0	103	101	99	98	101	100	98	96	98	96	95	94	95	93	92	91	87	

