

# 屋内照明器具特性

品番 (品名)	LGB11025	
光源	LED2700_70_293 x1	293.0 lm
管理番号	K0150710(0)DB1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	60	49	42	37	59	48	42	37	56	47	41	36	54	46	40	36	34
	中	0.63	0.8	70	60	52	47	68	59	52	47	65	57	51	46	63	55	50	46	44
	否	0.56	1.0	76	67	60	54	75	66	59	54	71	64	58	53	68	62	57	53	50
			1.25	82	73	67	62	80	72	66	61	77	70	65	60	74	68	63	59	57
下方投影面積	cm <sup>2</sup>		1.5	86	78	72	67	84	76	71	66	80	74	69	65	77	72	68	64	61
	等価発光面積		2.0	91	84	79	74	89	83	78	74	85	80	76	72	82	78	74	71	68
取付高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	79	88	84	80	77	85	82	78	76	72
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	94	90	86	82	91	87	83	81	87	84	81	79	76
Hm	1.22Hm	1.22Hm	4.0	99	95	91	88	97	93	90	87	93	90	88	85	90	88	85	83	80
			5.0	100	97	94	91	99	96	93	90	95	93	90	88	92	90	88	86	83
			7.0	102	100	97	95	100	98	96	94	97	95	94	92	94	93	91	90	86
			10.0	104	102	100	99	102	100	99	97	99	97	96	95	96	95	93	92	89

