

屋内照明器具特性

品番 (品名)	LGB11041									
光源	LED2700_70_331 x1					331.0 lm				
管理番号	K0153793(0)DB1									
BZ分類	BZ4/3.5/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	92%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	58	47	39	34	57	46	39	34	54	44	38	33	51	43	37	33	31
	中	0.63	0.8	68	58	50	45	66	57	50	45	63	55	48	44	60	53	47	43	40
	否	0.56	1.0	75	65	58	53	73	64	57	52	69	61	55	51	66	59	54	50	47
			1.25	80	71	64	59	78	70	64	59	74	67	62	57	70	65	60	56	53
下方投影面積		cm ²	1.5	84	76	69	64	82	74	68	63	78	71	66	62	74	68	64	60	57
等価発光面積		cm ²	2.0	89	82	76	71	87	80	75	71	82	77	73	69	78	74	70	67	63
取付高さ	器具間隔最大限		2.5	92	86	81	77	90	84	79	75	85	81	77	73	81	78	74	71	67
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	83	79	88	84	80	77	84	80	77	75	70
Hm	1.21Hm	1.21Hm	4.0	97	93	89	85	95	91	87	84	90	87	84	82	86	84	81	79	75
			5.0	99	95	92	89	96	93	90	87	92	90	87	85	88	86	84	82	77
			7.0	101	98	95	93	99	96	94	92	94	92	90	89	90	89	87	86	81
			10.0	102	100	98	97	100	98	97	95	96	95	93	92	92	91	90	89	84

