

屋内照明器具特性

品番 (品名)	LGB11006									
光源	LED2700_70_331 x1					331.0 lm				
管理番号	K0150804(0)DB1									
BZ分類	BZ4/8.5/BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 6%		反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
下方光束 94%	室指数	照明率 (X0.01)																ZCM			
保守率	良	0.67	0.6	58	47	39	34	57	46	39	34	54	45	38	34	51	43	37	33	31	
	中	0.63	0.8	69	58	51	45	67	57	50	45	64	55	49	44	61	53	48	44	41	
	否	0.56	1.0	75	66	59	53	74	65	58	53	70	62	57	52	67	60	55	51	49	
			1.25	81	72	66	61	79	71	65	60	76	69	63	59	72	67	62	58	55	
下方投影面積			1.5	85	77	71	66	83	76	70	65	79	73	68	64	76	71	66	63	60	
	等価発光面積		2.0	90	83	78	74	88	82	77	73	84	79	75	71	81	77	73	70	66	
取付高さ	器具間隔最大限		2.5	93	88	83	79	91	86	82	78	87	83	79	76	84	80	77	74	71	
	Hm	1.25Hm	3.0	95	90	86	82	93	89	85	81	90	86	82	79	86	83	80	78	74	
			4.0	98	94	91	87	96	93	89	86	92	89	87	84	89	86	84	82	78	
			5.0	100	96	93	91	98	95	92	89	94	92	89	87	91	89	87	85	81	
			7.0	102	99	97	95	100	98	95	93	96	94	92	91	93	91	90	88	84	
			10.0	103	101	100	98	101	100	98	97	98	96	95	94	94	93	92	91	87	

