

屋内照明器具特性	
品番 (品名)	LGB11092
光源	LED2700_70_342 x1 342.0 l m
管理番号	K0147053(0)DB1
BZ分類	BZ4/2.3/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	6%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	58	47	39	34	57	46	39	34	54	44	38	33	51	43	37	33	31
	中	0.63	0.8	68	57	49	44	66	56	49	43	63	54	47	43	60	52	46	42	40
	否	0.56	1.0	74	64	56	51	72	62	56	50	68	60	54	49	65	58	53	49	46
			1.25	79	70	63	58	77	69	62	57	74	66	61	56	70	64	59	55	52
下方投影面積		cm ²	1.5	83	75	68	63	81	74	67	62	77	71	66	61	74	68	64	60	57
等価発光面積		cm ²	2.0	89	82	76	71	87	80	75	70	83	77	72	69	79	74	70	67	64
取付高さ	器具間隔最大限		2.5	92	86	81	76	90	84	79	75	86	81	77	74	82	78	75	72	68
	横方向 (A)	縦方向 (B)	3.0	94	89	84	80	92	87	83	79	88	84	80	77	85	81	78	75	72
Hm	1.29Hm	1.29Hm	4.0	97	93	89	86	95	91	88	84	91	88	85	82	88	85	82	80	76
			5.0	99	95	92	89	97	94	91	88	93	90	88	86	90	87	85	83	79
			7.0	101	98	96	94	99	97	94	92	95	93	91	90	92	90	88	87	83
			10.0	103	101	99	97	101	99	97	96	97	96	94	93	94	92	91	90	86

