

屋内照明器具特性	
品番 (品名)	LGB15061WZ
光源	LDA7L-G / Z60E / S / W / 2 × 1 810.0 l m
管理番号	K0126485 (0) DB 1
BZ分類	BZ8

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	38 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	53 %		10 %				10 %				10 %				10 %				0 %	
室指数		照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6	4.2	3.0	2.3	1.8	3.8	2.8	2.2	1.7	3.3	2.4	1.9	1.5	2.7	2.1	1.6	1.2	8	
	中 0.6	0.8	4.9	3.8	3.0	2.5	4.6	3.5	2.8	2.3	3.9	3.0	2.5	2.0	3.2	2.6	2.1	1.7	1.2	
	否 0.56	1.0	5.5	4.4	3.6	3.0	5.0	4.1	3.4	2.8	4.3	3.5	2.9	2.5	3.6	3.0	2.5	2.1	1.5	
		1.25	6.0	5.0	4.2	3.6	5.5	4.6	3.9	3.4	4.7	4.0	3.4	3.0	3.9	3.4	2.9	2.5	1.8	
下方投影面積	cm ²	1.5	6.3	5.4	4.6	4.1	5.9	5.0	4.4	3.8	5.0	4.3	3.8	3.3	4.2	3.7	3.2	2.9	2.1	
等価発光面積		2.0	6.8	6.0	5.3	4.8	6.3	5.6	5.0	4.5	5.4	4.8	4.3	3.9	4.6	4.1	3.7	3.4	2.5	
取付高さ	器具間隔最大限		2.5	7.2	6.4	5.8	5.3	6.7	6.0	5.5	5.0	5.7	5.2	4.7	4.4	4.8	4.4	4.1	3.7	2.8
	横方向 (A)	縦方向 (B)	3.0	7.4	6.8	6.2	5.7	6.9	6.3	5.8	5.4	5.9	5.5	5.1	4.7	5.0	4.7	4.3	4.0	3.0
H _m	1.50H _m	1.50H _m	4.0	7.7	7.2	6.7	6.3	7.2	6.7	6.3	5.9	6.2	5.8	5.5	5.2	5.3	5.0	4.7	4.5	3.4
			5.0	7.9	7.5	7.0	6.6	7.4	7.0	6.6	6.3	6.4	6.1	5.8	5.5	5.5	5.2	5.0	4.8	3.6
			7.0	8.2	7.8	7.5	7.1	7.7	7.3	7.0	6.7	6.7	6.4	6.1	5.9	5.7	5.5	5.3	5.1	3.9
			10.0	8.4	8.1	7.8	7.6	7.9	7.6	7.4	7.1	6.9	6.7	6.5	6.3	5.9	5.8	5.6	5.5	4.2

