

屋内照明器具特性

品番 (品名)	LGB15371K															
光源	LDG11L-G/95/W x1 1370.0 lm															
管理番号	K0147993(0)DB1															
BZ分類	BZ6/1.1/BZ5															

器具効率	84%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	21%	室指数	照明率 (X0.01)																ZCM		
下方光束	63%																				
保守率	良 中 否 0.67 0.63 0.56	0.6	41	31	24	19	39	30	23	19	35	27	22	18	32	25	20	16	13		
		0.8	50	40	33	28	47	38	32	27	42	35	29	25	38	32	27	24	20		
		1.0	55	46	39	34	53	44	38	33	47	40	35	31	43	37	32	29	25		
		1.25	61	52	46	41	58	50	44	39	52	46	41	37	47	42	38	35	30		
下方投影面積	c m ²	1.5	65	57	51	46	61	54	49	44	56	50	45	42	50	46	42	39	34		
		2.0	70	63	58	53	66	61	56	52	60	56	52	48	55	51	48	45	39		
取付高さ	器具間隔最大限		2.5	73	67	63	59	70	65	60	57	64	60	56	53	58	55	52	49	43	
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	72	67	64	60	66	62	59	56	60	57	55	53	46	
H m	1.70 H m	1.70 H m	4.0	78	74	71	68	74	71	68	65	68	66	63	61	63	60	58	57	50	
			5.0	79	76	73	71	76	73	71	68	70	68	66	64	64	62	61	59	52	
			7.0	81	79	77	75	78	76	74	72	72	70	69	67	66	65	64	62	55	
			10.0	83	81	79	78	80	78	77	75	73	72	71	70	68	67	66	65	57	

