

屋内照明器具特性

品番 (品名)	LGB15540	
光源	LED3500_70_485 x1	485.0 lm
管理番号	K0151381(0)DB1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	56	43	35	30	54	42	35	30	51	41	34	29	49	40	34	29	27
	中	0.6	0.8	65	54	46	40	64	53	45	40	61	51	44	39	58	50	43	39	36
	否	0.56	1.0	72	61	53	47	70	60	53	47	67	58	52	46	64	56	50	46	43
			1.25	78	68	61	55	76	67	60	55	73	65	59	54	69	63	57	53	50
下方投影面積		cm ²	1.5	82	73	66	61	80	72	65	60	77	70	64	59	73	67	62	58	55
等価発光面積		cm ²	2.0	88	80	74	69	86	79	73	68	82	76	71	67	79	74	70	66	63
取付高さ	器具間隔最大限		2.5	92	85	79	75	90	84	78	74	86	81	76	73	82	78	74	71	68
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	77	85	81	78	75	72
Hm	1.30Hm	1.30Hm	4.0	97	93	89	85	95	91	87	84	92	88	85	82	88	86	83	80	77
			5.0	99	95	92	89	97	94	91	88	94	91	88	86	91	88	86	84	80
			7.0	101	99	96	93	100	97	95	92	96	94	92	90	93	91	90	88	84
			10.0	103	101	99	97	101	100	98	96	98	97	95	94	95	94	92	91	87

