

# 屋内照明器具特性

品番 (品名)	LGB15285									
光源	LED2700_70_415 x1					415.0 lm				
管理番号	K0151380(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
		床	10%				10%				10%				10%				0%			
上方光束	3%																					
下方光束	97%																					
室指数	照明率 ( X0.01 )																		ZCM			
保守率	良 中 否	0.63	0.6	0.56	0.6	56	43	35	30	54	42	35	30	51	41	34	29	49	40	34	29	27
		0.6	0.8	66	54	46	40	64	53	45	40	61	51	44	39	58	50	44	39	37		
		1.0	72	61	53	47	70	60	53	47	67	58	52	47	64	56	51	46	43			
		0.56	1.25	78	68	61	55	76	67	60	55	73	65	59	54	70	63	57	53	50		
下方投影面積	c m <sup>2</sup>	1.5	82	73	66	60	80	72	65	60	77	70	64	59	74	68	62	58	55			
		2.0	88	80	74	69	86	79	73	68	83	77	71	67	79	74	70	66	63			
取付高さ	器具間隔最大限		2.5	92	85	79	75	90	84	78	74	86	81	77	73	83	79	75	71	68		
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	89	84	80	77	85	82	78	75	72		
H m	1.30H m	1.30H m	4.0	97	93	89	85	95	91	87	84	92	89	85	82	89	86	83	81	77		
			5.0	99	95	92	89	97	94	91	88	94	91	88	86	91	89	86	84	81		
			7.0	102	99	96	93	100	97	95	92	97	94	92	90	94	92	90	88	85		
			10.0	103	101	99	97	102	100	98	96	99	97	95	94	96	94	93	92	88		

