

屋内照明器具特性	
品番 (品名)	S L B 5 0 6 4 0
光源	LED3500_70_2750 ×1 2750.0 lm
管理番号	K0146929 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 5 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		8 5 %																							
保守率		良 中 否	0 . 6 9	0 . 6	5 2	3 9	3 1	2 5	4 9	3 8	3 0	2 5	4 6	3 5	2 9	2 4	4 2	3 3	2 7	2 3	2 0				
			0 . 6 7	0 . 8	6 1	4 9	4 0	3 4	5 8	4 7	3 9	3 4	5 4	4 4	3 7	3 2	5 0	4 2	3 6	3 1	2 7				
			0 . 6 3	1 . 0	6 7	5 6	4 7	4 1	6 4	5 4	4 6	4 0	5 9	5 0	4 4	3 8	5 5	4 7	4 1	3 7	3 3				
				1 . 2 5	7 3	6 2	5 4	4 8	7 0	6 0	5 3	4 7	6 5	5 6	5 0	4 5	6 0	5 3	4 7	4 3	3 8				
下方投影面積		c m ²	1 . 5	7 7	6 7	5 9	5 3	7 4	6 5	5 8	5 2	6 9	6 1	5 5	5 0	6 3	5 7	5 2	4 8	4 3					
			等価発光面積	c m ²	2 . 0	8 3	7 4	6 7	6 1	8 0	7 2	6 5	6 0	7 4	6 7	6 2	5 7	6 9	6 3	5 9	5 5	4 9			
取付高さ	器具間隔最大限		2 . 5	8 6	7 9	7 3	6 7	8 3	7 6	7 1	6 6	7 8	7 2	6 7	6 3	7 2	6 7	6 3	6 0	5 4					
	横方向 (A) 縦方向 (B)		3 . 0	8 9	8 2	7 7	7 2	8 6	8 0	7 5	7 0	8 0	7 5	7 1	6 7	7 5	7 0	6 7	6 3	5 8					
1 . 5 m	2 . 0 9 m	2 . 1 6 m	4 . 0	9 3	8 7	8 2	7 8	8 9	8 4	8 0	7 6	8 4	7 9	7 6	7 2	7 8	7 5	7 2	6 9	6 3					
2	2 . 7 6	2 . 7 3	5 . 0	9 5	9 0	8 6	8 2	9 2	8 7	8 3	8 0	8 6	8 2	7 9	7 6	8 0	7 7	7 5	7 2	6 6					
2 . 5	3 . 4 4	3 . 3 2	7 . 0	9 7	9 4	9 0	8 7	9 4	9 1	8 8	8 5	8 8	8 6	8 3	8 1	8 3	8 1	7 9	7 7	7 0					
3	4 . 1	3 . 9 2	1 0 . 0	9 9	9 7	9 4	9 2	9 6	9 4	9 1	8 9	9 1	8 9	8 7	8 5	8 5	8 4	8 2	8 0	7 4					

