

屋内照明器具特性	
品番 (品名)	LGB16021WF
光源	LDA4L-H-E17/E/S/W/2×1440.0lm
管理番号	K0128989(0)DB1
BZ分類	BZ5/2.8/BZ4

器具効率		9 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 4	4 2	3 4	2 9	5 2	4 1	3 4	2 9	5 0	4 0	3 3	2 9	4 8	3 9	3 3	2 8	2 7
			0 . 6 3	0 . 8	6 4	5 2	4 5	3 9	6 2	5 2	4 4	3 9	5 9	5 0	4 4	3 9	5 7	4 9	4 3	3 9	3 6
			0 . 5 6	1 . 0	7 0	6 0	5 2	4 7	6 9	5 9	5 2	4 6	6 6	5 7	5 1	4 6	6 3	5 6	5 0	4 6	4 4
				1 . 2 5	7 6	6 7	6 0	5 4	7 5	6 6	5 9	5 4	7 2	6 4	5 8	5 4	6 9	6 2	5 7	5 3	5 1
下方投影面積		c m ²	1 . 5	8 0	7 2	6 5	6 0	7 9	7 1	6 5	6 0	7 6	6 9	6 4	5 9	7 3	6 7	6 3	5 9	5 6	
			等価発光面積	2 . 0	8 6	7 9	7 3	6 8	8 4	7 8	7 2	6 8	8 1	7 6	7 1	6 7	7 9	7 4	7 0	6 6	6 4
取付 高さ	器具間隔最大限		2 . 5	8 9	8 3	7 8	7 4	8 8	8 2	7 8	7 4	8 5	8 0	7 6	7 3	8 2	7 8	7 5	7 2	6 9	
	横方向 (A) 縦方向 (B)		3 . 0	9 2	8 7	8 2	7 8	9 0	8 5	8 1	7 8	8 7	8 3	8 0	7 7	8 5	8 1	7 8	7 6	7 3	
H m	1 . 3 5 H m 1 . 3 2 H m		4 . 0	9 5	9 1	8 7	8 4	9 3	9 0	8 6	8 3	9 1	8 7	8 5	8 2	8 8	8 5	8 3	8 1	7 8	
			5 . 0	9 7	9 3	9 0	8 7	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 5	9 0	8 8	8 6	8 4	8 1	
			7 . 0	9 9	9 6	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	9 2	9 1	8 9	8 8	8 5	
			1 0 . 0	1 0 0	9 8	9 7	9 5	9 9	9 7	9 6	9 4	9 6	9 5	9 4	9 3	9 4	9 3	9 2	9 1	8 8	

