

屋内照明器具特性	
品番 (品名)	S L D 1 0 1 0 N
光源	LED5000_70_432 ×1 432.0 l m
管理番号	K0161908 (1) DB 1
B Z 分類	B Z 2

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 6 7	0 . 6	6 7	5 7	5 1	4 6	6 6	5 6	5 0	4 6	6 4	5 6	5 0	4 6	6 2	5 5	5 0	4 6	4 4				
			0 . 6 3	0 . 8	7 7	6 8	6 2	5 8	7 6	6 8	6 2	5 8	7 4	6 7	6 2	5 8	7 2	6 6	6 1	5 7	5 6				
			1 . 0	8 4	7 6	7 0	6 6	8 2	7 5	7 0	6 6	8 0	7 4	6 9	6 5	7 8	7 3	6 8	6 5	6 3					
			0 . 5 6	1 . 2 5	8 9	8 2	7 7	7 3	8 7	8 1	7 6	7 3	8 5	8 0	7 5	7 2	8 3	7 8	7 5	7 2	7 0				
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	9 2	8 6	8 1	7 8	9 1	8 5	8 1	7 7	8 8	8 4	8 0	7 7	8 6	8 2	7 9	7 6	7 4					
			2 . 0	9 6	9 1	8 7	8 4	9 5	9 0	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 4	8 2	8 0					
取付高さ	器具間隔最大限		2 . 5	9 9	9 5	9 1	8 8	9 7	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4					
	横方向 (A) 縦方向 (B)		3 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 4	9 2	9 0	8 8	8 6					
H m	1 . 1 5 H m 1 . 1 5 H m		4 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9					
			5 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 8	9 6	9 5	9 4	9 1					
			7 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4					
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 5					

