

# 屋内照明器具特性

品番 (品名)	LGB16449														
光源	LDA5L/C/W ×1					485.0 lm									
管理番号	K0172837(0)DB1														
BZ分類	BZ5														

器具効率	98%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	7%	反射率	床	10%				10%				10%				10%				0%
下方光束	91%		室指数	照明率 (×0.01) ZCM																
保守率	良 中 否 0.69 0.67 0.63	0.6	53	41	33	27	51	40	32	27	48	38	31	27	46	37	31	26	24	
		0.8	62	51	43	37	61	50	42	36	57	48	41	36	54	46	40	35	32	
		1.0	69	58	50	44	67	56	49	43	63	54	47	42	59	52	46	41	38	
		1.25	75	64	57	51	72	63	56	50	68	60	54	49	64	58	52	48	45	
下方投影面積	c m <sup>2</sup>	1.5	79	69	62	56	76	68	61	55	72	65	59	54	68	62	57	53	49	
		2.0	84	76	70	64	82	74	68	63	78	71	66	62	74	68	64	60	56	
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	79	74	69	81	76	71	67	77	73	69	65	
	横方向 (A)	縦方向 (B)	3.0	90	84	79	74	88	82	77	73	84	79	75	71	80	76	72	69	
H m	1.28 H m	1.28 H m	4.0	94	89	84	80	91	87	83	79	87	83	80	77	83	80	77	74	
			5.0	96	91	88	84	93	90	86	83	89	86	83	80	85	83	80	78	
			7.0	98	95	92	89	96	93	90	88	92	89	87	85	88	86	84	82	
			10.0	100	98	95	93	98	96	94	92	94	92	90	89	90	89	87	86	

