

屋内照明器具特性

品番 (品名)	LGB16796				
光源	LED2700_70_300 x1 300.0 l m				
管理番号	K0148374 (0) DB 1				
BZ分類	BZ4/6.0/BZ3				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	5.9	4.7	4.0	3.4	5.8	4.7	3.9	3.4	5.5	4.6	3.9	3.4	5.3	4.5	3.9	3.4	3.2
	中	0.63	0.8	6.9	5.9	5.1	4.6	6.8	5.8	5.1	4.6	6.5	5.7	5.0	4.5	6.3	5.5	5.0	4.5	4.3
	否	0.56	1.0	7.6	6.6	5.9	5.4	7.5	6.6	5.9	5.4	7.2	6.4	5.8	5.3	6.9	6.3	5.7	5.3	5.1
			1.25	8.2	7.4	6.7	6.2	8.1	7.3	6.6	6.1	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.1	5.8
下方投影面積	cm ²		1.5	8.6	7.9	7.2	6.7	8.5	7.8	7.2	6.7	8.2	7.6	7.1	6.7	7.9	7.4	7.0	6.6	6.4
等価発光面積	cm ²		2.0	9.2	8.6	8.0	7.6	9.0	8.5	8.0	7.5	8.8	8.3	7.8	7.5	8.5	8.1	7.7	7.4	7.2
取付高さ	器具間隔最大限		2.5	9.5	9.0	8.5	8.1	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.2	7.9	7.7
	横方向 (A)	縦方向 (B)	3.0	9.8	9.3	8.9	8.5	9.6	9.2	8.8	8.5	9.3	9.0	8.7	8.4	9.1	8.8	8.5	8.3	8.0
Hm	1.24Hm	1.24Hm	4.0	10.0	9.7	9.3	9.1	9.9	9.6	9.3	9.0	9.6	9.3	9.1	8.9	9.4	9.1	8.9	8.7	8.5
			5.0	10.2	9.9	9.6	9.4	10.1	9.8	9.5	9.3	9.8	9.6	9.4	9.2	9.6	9.4	9.2	9.0	8.8
			7.0	10.4	10.2	10.0	9.8	10.3	10.1	9.9	9.7	10.0	9.8	9.7	9.5	9.8	9.6	9.5	9.4	9.1
			10.0	10.5	10.4	10.2	10.1	10.4	10.3	10.1	10.0	10.2	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.4

