

屋内照明器具特性

品番 (品名)		NNLK41509J + NEL4300EN																					
光源		LED5000_85_3200 ×1 3200.0 lm																					
管理番号		K0192447 (0) DR 1																					
BZ分類		BZ5																					
器具効率 上方光束 下方光束		100 % 4 % 96 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
			室指数	照明率 (X0.01)																		Z CM	
保守率		良 中 否	0.83 0.81 0.77	0.6	55	43	35	30	54	42	35	30	51	41	34	29	49	40	33	29	27		
				0.8	65	54	46	40	63	53	45	39	60	51	44	39	57	49	43	38	36		
				1.0	72	61	53	47	70	60	52	47	66	58	51	46	63	56	50	45	42		
				1.25	78	68	60	54	76	66	59	54	72	64	58	53	68	62	56	52	49		
下方投影面積 等価発光面積		cm ² cm ²	1.5	82	72	65	60	80	71	64	59	76	69	63	58	72	66	61	57	54			
				2.0	87	79	73	68	85	78	72	67	81	75	70	66	78	73	68	64	61		
取付 高さ	器具間隔最大限			2.5	91	84	78	73	89	83	77	73	85	80	75	71	81	77	73	70	66		
	横方向 (A)		縦方向 (B)																				
1.5m	1.96 m	2.1 m	4.0	96	92	87	84	94	90	86	83	91	87	84	81	87	84	81	87	84	81	79	75
2	2.58	2.64																					
2.5	3.21	3.2																					
3	3.84	3.77																					
				10.0	103	100	98	96	101	99	97	95	97	96	94	92	94	92	91	90	86		

