

# 屋内照明器具特性

|         |                     |  |  |  |  |          |  |  |  |  |
|---------|---------------------|--|--|--|--|----------|--|--|--|--|
| 品番 (品名) | LGB16743            |  |  |  |  |          |  |  |  |  |
| 光源      | LED2700_70_340 x1   |  |  |  |  | 340.0 lm |  |  |  |  |
| 管理番号    | K0153794(0)DB1      |  |  |  |  |          |  |  |  |  |
| BZ分類    | BZ4/1.8/BZ5/6.0/BZ6 |  |  |  |  |          |  |  |  |  |

|        |               |         |      |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |     |    |
|--------|---------------|---------|------|-----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|-----|----|
| 器具効率   | 100%          | 天井      | 80%  |     |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |     |    |
|        | 上方光束          |         | 12%  | 反射率 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10  | 0% |
|        | 下方光束          |         | 88%  |     | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |     |    |
| 室指数    | 照明率 ( X0.01 ) |         |      |     |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    | ZCM |    |
| 保守率    | 良             | 0.67    | 0.6  | 58  | 47 | 40  | 35  | 57 | 46 | 39  | 34  | 53 | 44 | 38  | 34  | 50 | 42 | 37  | 33 | 30  |    |
|        | 中             | 0.63    | 0.8  | 68  | 58 | 50  | 45  | 66 | 56 | 49  | 45  | 62 | 54 | 48  | 43  | 58 | 51 | 46  | 42 | 39  |    |
|        | 否             | 0.56    | 1.0  | 74  | 64 | 57  | 52  | 72 | 63 | 56  | 51  | 68 | 60 | 54  | 50  | 64 | 57 | 53  | 49 | 45  |    |
|        |               |         | 1.25 | 79  | 70 | 63  | 58  | 77 | 68 | 62  | 57  | 72 | 65 | 60  | 56  | 68 | 62 | 58  | 54 | 50  |    |
| 下方投影面積 |               |         | 1.5  | 82  | 74 | 68  | 62  | 80 | 72 | 66  | 61  | 75 | 69 | 64  | 59  | 71 | 66 | 61  | 58 | 53  |    |
|        | 等価発光面積        |         | 2.0  | 87  | 79 | 73  | 69  | 84 | 78 | 72  | 67  | 79 | 74 | 69  | 65  | 75 | 70 | 66  | 63 | 58  |    |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 90  | 83 | 78  | 73  | 87 | 81 | 76  | 72  | 82 | 77 | 73  | 69  | 77 | 73 | 70  | 66 | 62  |    |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 92  | 86 | 81  | 76  | 89 | 84 | 79  | 75  | 84 | 79 | 75  | 72  | 79 | 75 | 72  | 69 | 64  |    |
| Hm     | 1.19Hm        | 1.19Hm  | 4.0  | 94  | 89 | 85  | 81  | 92 | 87 | 83  | 79  | 87 | 83 | 79  | 76  | 82 | 79 | 76  | 73 | 68  |    |
|        |               |         | 5.0  | 96  | 92 | 88  | 84  | 94 | 90 | 86  | 83  | 88 | 85 | 82  | 79  | 83 | 81 | 78  | 76 | 70  |    |
|        |               |         | 7.0  | 98  | 95 | 92  | 89  | 96 | 93 | 90  | 87  | 91 | 88 | 86  | 83  | 86 | 84 | 82  | 80 | 74  |    |
|        |               |         | 10.0 | 100 | 98 | 95  | 93  | 98 | 95 | 93  | 91  | 93 | 91 | 89  | 87  | 88 | 86 | 85  | 83 | 77  |    |

