

屋内照明器具特性	
品番 (品名)	LGB19331BZ
光源	LDA7L-G/Z60E/S/W/2 × 3 810.0 l m
管理番号	K0126472(0)DB1
BZ分類	BZ8

器具効率	90%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	38%	室指数	床	10%				10%				10%				10%				0%
下方光束	52%		照明率 (X0.01) ZCM																	
保守率	良 0.63	0.6	4.1	3.0	2.3	1.8	3.8	2.8	2.1	1.7	3.2	2.4	1.8	1.4	2.7	2.0	1.6	1.2	0.8	
	中 0.6	0.8	4.9	3.8	3.0	2.5	4.5	3.5	2.8	2.3	3.8	3.0	2.4	2.0	3.2	2.5	2.1	1.7	1.2	
	否 0.56	1.0	5.4	4.3	3.6	3.0	5.0	4.0	3.3	2.8	4.2	3.5	2.9	2.4	3.5	2.9	2.5	2.1	1.4	
		1.25	5.9	4.9	4.2	3.6	5.5	4.6	3.9	3.4	4.6	3.9	3.4	2.9	3.9	3.3	2.9	2.5	1.8	
下方投影面積	cm ²	1.5	6.3	5.3	4.6	4.0	5.8	5.0	4.3	3.8	4.9	4.3	3.7	3.3	4.1	3.6	3.2	2.8	2.0	
		2.0	6.8	6.0	5.3	4.7	6.3	5.6	5.0	4.5	5.4	4.8	4.3	3.9	4.5	4.0	3.7	3.3	2.4	
取付高さ	器具間隔最大限		2.5	7.1	6.4	5.8	5.3	6.6	6.0	5.4	4.9	5.7	5.1	4.7	4.3	4.8	4.4	4.0	3.7	2.7
	横方向 (A)	縦方向 (B)	3.0	7.4	6.7	6.1	5.7	6.9	6.3	5.8	5.3	5.9	5.4	5.0	4.6	5.0	4.6	4.3	4.0	2.9
H _m	1.54H _m	1.55H _m	4.0	7.7	7.1	6.7	6.2	7.2	6.7	6.2	5.8	6.2	5.8	5.4	5.1	5.2	4.9	4.7	4.4	3.3
			5.0	7.9	7.4	7.0	6.6	7.4	6.9	6.6	6.2	6.4	6.0	5.7	5.4	5.4	5.2	4.9	4.7	3.5
			7.0	8.1	7.8	7.4	7.1	7.6	7.3	7.0	6.7	6.6	6.3	6.1	5.9	5.7	5.4	5.2	5.1	3.9
			10.0	8.3	8.1	7.8	7.5	7.8	7.6	7.3	7.1	6.8	6.6	6.4	6.2	5.8	5.7	5.5	5.4	4.1

