

屋内照明器具特性	
品番 (品名)	LGB19561BK
光源	LDA7L-G / Z60E / S / W / 2 × 5      810.0 l m
管理番号	K0140283 ( 0 ) DB 1
BZ分類	BZ8

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	39 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	40	29	22	17	37	27	20	16	31	23	18	14	26	19	15	11	7
	中	0.6	0.8	48	37	29	24	44	34	27	22	37	29	23	19	30	24	20	16	11
	否	0.56	1.0	53	42	35	29	49	39	32	27	41	33	28	23	34	28	23	20	13
			1.25	58	48	40	35	53	45	38	32	45	38	32	28	37	32	27	24	16
下方投影面積		cm <sup>2</sup>	1.5	62	52	45	39	57	48	42	37	48	41	36	32	40	35	30	27	19
等価発光面積		cm <sup>2</sup>	2.0	67	58	52	46	62	54	48	43	52	46	42	37	43	39	35	32	23
取付高さ	器具間隔最大限		2.5	70	63	57	51	65	58	53	48	55	50	45	42	46	42	39	35	25
	横方向 (A)	縦方向 (B)	3.0	72	66	60	55	67	61	56	52	57	53	49	45	48	44	41	38	28
Hm	1.68Hm	1.36Hm	4.0	75	70	65	61	70	65	61	57	60	56	53	50	51	48	45	42	31
			5.0	77	73	69	65	72	68	64	61	62	59	56	53	52	50	47	45	34
			7.0	80	76	73	70	75	71	68	65	64	62	59	57	55	53	51	49	37
			10.0	82	79	76	74	77	74	72	69	66	64	62	61	57	55	54	52	39

