

屋内照明器具特性	
品番(品名)	LGB19261BZ
光源	LDA7L-G/Z60E/S/W/2 × 2 810.0 l m
管理番号	K0126481(0)DB1
BZ分類	BZ8

器具効率	89%	反射率	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	42%	室指数	床	10%				10%				10%				10%				0%	
下方光束	47%		照明率 ( X0.01 )																ZCM		
保守率	良 0.63	0.6	0.6	40	29	22	17	37	27	20	16	31	23	17	14	25	19	14	11	7	
	中 0.6		0.8	48	37	29	24	44	34	27	22	36	29	23	19	30	24	19	16	10	
	否 0.56		1.0	53	42	35	29	49	39	32	27	40	33	27	23	33	27	23	19	13	
			1.25	58	48	40	35	53	44	38	32	44	37	32	28	36	31	27	23	15	
下方投影面積	cm <sup>2</sup>	等価発光面積	cm <sup>2</sup>	1.5	61	52	45	39	56	48	42	37	47	41	36	31	39	34	30	26	18
				2.0	66	58	52	46	61	54	48	43	51	46	41	37	42	38	34	31	21
取付高さ	器具間隔最大限		H m	2.5	70	62	56	51	64	58	52	48	54	49	45	41	45	41	37	34	24
	横方向(A)	縦方向(B)		3.0	72	66	60	55	67	61	56	51	56	52	48	44	47	43	40	37	26
	1.59H m	1.59H m	4.0	75	70	65	61	70	65	61	57	59	55	52	49	49	46	44	41	29	
			5.0	77	72	68	64	72	67	64	60	61	58	55	52	51	48	46	44	32	
			7.0	80	76	73	69	74	71	68	65	63	61	58	56	53	51	49	48	35	
			10.0	82	79	76	74	76	73	71	69	65	63	61	60	55	54	52	51	37	

